

-40°C Biomedical Freezer

Model: MDF-40V278W

(Version: 2024-5)



Applications

The -40 °C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.

Features

- Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C
- HC green refrigerant is energy-saving and environmentally friendly.
- Wide available voltage range: 187V~242V.

Security

- Safety door lock and controller password to prevent unauthorized access.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

- Drawers for easy storage.
- Casters with stoppers for easy moving and fixation.



Specifications

Model NO.	MDF-40V278W
Main Specif	ications
Temperature Range	-20 ~ -40 °C
Ambient Temperature	10~32℃
Capacity (L/Cu. Ft.)	278 / 9.82
Interior Dimensions (W×D×H) mm	480×415×1460
Exterior Dimensions (W×D×H) mm	659×600×1694
Weight	110 kgs
Noise	50 dB
Control and	d Power
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	187~242V, 50/60Hz
Power	280 W
Electric Current	1.48 A
Power Consumption (kWh/24h)	5.2
Audible and Vi	sual Alarms
High / Low Temp. Alarm	Yes
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigera	ation
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	CUBIGEL / 1
Refrigerant / Weight (kgs)	R290 / 49g
Cabin	et
Door (pcs)	Foamed Solid Door / 1
Drawer (pcs)	7
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ85.5mm)
Door Lock	Yes
Test Hole (pcs)	Ф25mm / 1
Fixed / Levelling Castors (pcs)	4 / 0
Accesso	pries
Voltage Stabilizer	Optional
Temperature Datalogger	Optional
Shippi	ng
Package	Carton box with pallet
Shipping Weight	125 kgs
Shipping Size (W×D×H)	710×650×1800
Shipping Volume	0.83 CBM