

2~8°C



Biomedical Refrigerator (Forced-air Cooling System)

Model: MPC-5V100A

(Version: 2024-5)



Applications

2~8°C biomedical refrigerators are specially designed to store medicines, vaccines, reagents, and bio-medical products.

Features

- Microprocessor control, ensure the inside temperature is within 2~8°C, accuracy is 0.1°C
- Suggested ambient temperature: +10~32°C.
- Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
- Foamed solid door provides dark storage condition.
- Wide available voltage range: 187V~242V.

Security

- Safety door lock and controller password to prevent unauthorized access.
- 8h built-in backup battery to power the controller and save temp. data when power failure or system error.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

- Special designed service-free drainage system, ensure no water in the cabinet.
- Adjustable shelves for easy storage.
- Auto on/off LED light with manual switch on the control panel.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.



Specifications

Model NO.	MPC-5V100A
Main Specifications	
Temperature Range	2 ~ 8 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	100 / 3.53
Interior Dimensions (W×D×H) mm	385×356×737
Exterior Dimensions (W×D×H) mm	505×525×900
Weight	30 kgs
Noise	50 dB
Control and Power	
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	187~242V, 50/60Hz
Power	91 W
Electric Current	0.8 A
Power Consumption (kWh/24h)	0.53
Audible and Visual Alarms	
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration	
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	Chinese Brand / 1
Refrigerant / Weight (kgs)	R600a / 30g
Cabinet	
Door (pcs)	Foamed Solid Door / 1
Fixed / Adjustable Shelf (pcs)	0 / 3
Interior Cabinet Material	HIPS
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ65mm)
Door Lock	Yes
LED Lamp	Yes
Fixed / Levelling Feet (pcs)	4 / 0
Accessories	
Voltage Stabilizer	Optional
Temperature Datalogger	Optional
Shipping	
Package	Carton box
Shipping Weight	33 kgs
Shipping Size (W×D×H)	580×580×940
Shipping Volume	0.32 CBM