

2~8°C



Biomedical Refrigerator (Forced-air Cooling System)

Model: MPC-5V236

(Version: 2024-5)



Applications

2~8°C biomedical refrigerators are specially designed to store medicines, vaccines, reagents, and bio-medical products.

Features

- Microprocessor control, ensure the inside temperature is within 2~8°C, accuracy is 0.1°C
- Suggested ambient temperature: +10~32°C.
- Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
- Wide available voltage range: 187V~242V.

Security

- Safety door lock and controller password to prevent unauthorized access.
- 8h built-in backup battery to power the controller and save temp. data when power failure or system error.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

- Special designed service-free drainage system, ensure no water in the cabinet.
- Adjustable shelves for easy storage.
- Casters with stoppers for easy moving and fixation.
- Auto on/off LED light with manual switch on the control panel.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.



LED Light, Controller



Test Hold, Adjustable Shelf

Specifications

Model NO.	MPC-5V236
Main Specifications	
Temperature Range	2 ~ 8 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	236 / 8.33
Interior Dimensions (W×D×H) mm	534×406×1150
Exterior Dimensions (W×D×H) mm	625×574×1707
Weight	73 kgs
Noise	50 dB
Control and Power	
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	187~242V, 50/60Hz
Power	221 W
Electric Current	1.4 A
Power Consumption (kWh/24h)	1.6
Audible and Visual Alarms	
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration	
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	Chinese Brand / 1
Refrigerant / Weight (kgs)	R600a / 116g
Cabinet	
Door (pcs)	LOW-E Glass Door / 1
Fixed / Adjustable Shelf (pcs)	0 / 4
Interior Cabinet Material	ABS
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ45mm)
Door Lock	Yes
LED Lamp	Yes
Test Hole (pcs)	Φ25mm / 1
Fixed / Levelling Castors (pcs)	4 / 0
Fixed / Levelling Feet (pcs)	0 / 2
Accessories	
Voltage Stabilizer	Optional
USB Data Download Port	Optional
Remote Alarm Port	Optional
RS232 / RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Shipping	
Package	Carton box with pallet
Shipping Weight	76 kgs
Shipping Size (W×D×H)	707×676×1820
Shipping Volume	0.87 CBM