Table Top Steam Sterilizer





Use

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culturemedium and biological dressing, food, etc.

Characteristics

- ◆ For 4~6 minutes rapidly sterilizin.
- ◆ Digital display of working status, touch type key.
- ◆ With 3 fixed cycles of sterilizing program and adjustable for user.
- The whole process of water adding, temperaturerising, sterilizing, drying steam discharging controlled automatically.
- Steam—water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
- Safe protection of water lacking.
- Exhaust the cool air automatically.
- ◆ Door safety lock system.
- With four stainless steel sterilizing plates.
- ◆ The chamber of the sterilizer is made of stainless steel.
- ◆ Automatically shut off with beep reminding after sterilization.
- With drying function.

Technical Data

MODEL Technical Data	TM-XD35D	TM-XD50D
Sterilizing chamber volume	35L ф 300 × 500mm	50L φ 340 × 550mm
Working pressure	0.22MPa	
Working temperature	134℃	
Temperature adjust range	105~134℃	
Timer range	0~99min	
Heat average	≤ ±1°C	
Power	2.7KW / AC220V.50Hz	
Sterilizing plate(mm)	400 × 200 × 30(4piece)	500 × 250 × 30(4piece)
Dimension(mm)	730×550×510	770×600×540
Exterior package dimension(mm)	780 × 670 × 650	840×710×690
G.W/N.W	92kg / 78kg	105kg / 89kg